

CDO-8000

KEY FEATURES:

- ~8g/hr. output
- Mobility
- Instant on
- Easy to use
- Built in O₂ concentrator
- Powder coated cabinet

PRODUCT DESCRIPTION

The CDO-8000 is an all in one solution, ozone generator / oxygen generator. It is ideal for mobile applications because it does not require warm up time like the SNOA series.



AZCO INDUSTRIES LIMITED
ADVANCED OZONE TECHNOLOGY



SPECIFICATIONS

	CDO-8000 (E*)	SNOA-4 (E*)	SNOA-2 (E*)
General			
Voltage [VAC, 50/60Hz]	100-120 (200-240)		
Power Consumption [W]	720	200	80
Ambient Temperature [°C]	2 to 28		
Relative Humidity [%]	10 to 92 (non-condensing)	10-80 (non-condensing)	
Mass [Kg]	42 (44.6)	8.6 (9.9)	6.5 (7.7)
Dimensions [L x W x H] [mm] <small>1 mm = .039 inches</small>	534 x 305 x 915	514 x 305 x 196	546 x 266 x 115
Installation	Refer to AZCO's installation manual for specific product		
Warranty [Refer to AZCO warranty sheet]	3 year		
Ozone			
Generation Process	Pulse, Corona Discharge		
Process Gas [bar] <small>1 bar = 14.5 psi</small>	Oxygen	dry air free of dust and oil. Maximum pressure +/- 0.36	
Production [Refer to Graph for more detail]	~ 8.0 g/hr.	~ 4.0 g/hr	~ 2.0 g/hr
Options			
Internal Air Pump	N/A	O	O (N/A)
Adjustable Output	N/A	O	O
Interlock	N/A	O	O
Flow Meter	N/A	S	O
Oxygen Ready	S	N/A	N/A
Vacuum Switch	N/A	S	N/A
Built-in Air Dryer	S (Oxygen Concentrator)	S	S
Safety			



E*: European Version, N/A: Not Applicable, O: Optional, S: Standard